

Mating receptical to be assembled as a set





Connector A Manfacturer - JST Part #s S2B-PH-K-S Plug entry view



Connector B Manfacturer - JST Part #s PHR-2 Crimp Pin Part # SPH-002T-P0.5S Or equivalent Wire Entry View **Scale 5.00** 


Tolerances. Unless noted-0.0 +/-

0.00 +/-0.000 +/-


| Connector A Pin | Connector B Pin | Wire Type              |                           |                                  |  |  |
|-----------------|-----------------|------------------------|---------------------------|----------------------------------|--|--|
| 1               | 1               | Braided 24 AWG - Red   |                           | JST_3-PIN_WITH_WIREOUTS          |  |  |
| 2               | 2               | Braided 24 AWG - Black | IST 3-PIN                 |                                  |  |  |
|                 |                 |                        |                           |                                  |  |  |
|                 |                 |                        |                           |                                  |  |  |
|                 |                 | Sheilding and cable    |                           |                                  |  |  |
|                 |                 | jacket type are not    | Units In                  | Drawn by Spark Fun Electronics   |  |  |
|                 |                 | of importance.         | Utilis iti                | Drawn by Spark I dif Electronics |  |  |
|                 |                 |                        | 20 Apr 10                 | for Price Quote                  |  |  |
|                 |                 |                        | 20 Apr 10 for Price Quote | 101 The Quote                    |  |  |
|                 |                 |                        | Toloropoo I/ 0 125        | Drofton IIII Cools 1.25          |  |  |
|                 |                 |                        | Tolerance +/- 0.125       | Drafter HH Scale 1.25            |  |  |

Mating receptical to be assembled as a set





Connector A
Manfacturer - JST
Part #s S3B-PH-K-S... S5B-PH-K-S
Or equivalent
Plug entry view



Connector B
Manfacturer - JST
Part #s PHR-3...PHR-5
Crimp Pin Part # SPH-002T-P0.5S
Or equivalent
Wire Entry View
Scale 5.00

Tolerances, Unless noted-0.0 +/-

0.00 +/-0.000 +/-

| Connector A Pin | Connector B Pin | Wire Type                               |                         | <u>.</u>                       |  |
|-----------------|-----------------|---|-------------------------|--------------------------------|--|
| 1               | 1               | Braided 24 AWG - Yellow                 | JST_3-PIN_WITH_WIREOUTS |                                |  |
| 2               | 2               | Braided 24 AWG - Black                  |                         |                                |  |
| 3               | 3               | Braided 24 AWG - Red                    |                         |                                |  |
| 4               | 4               | Braided 24 AWG - Blue                   |                         |                                |  |
| 5               | 5               | Braided 24 AWG - Green                  |                         |                                |  |
|                 |                 |   | Units in                | Drawn by Spark Fun Electronics |  |
|                 |                 | Sheilding and cable jacket type are not | 20 Apr 10               | for Price Quote                |  |
|                 |                 | of importance.                          | Tolerance +/- 0.125     | Drafter HH Scale 1.25          |  |

| Set number | Part Numbers<br>(Parts from JST or equivalent)                          | Notes  | Page 3 / 3   |  |
|------------|---|--|--|--|
| 1          | 1 x S2B-PH-K-S<br>1 x PHR-2<br>2 x SPH-002T-P0.5S<br>2 x Braided 24 AWG | Wire colors and order given on sheet 1   |  |  |
| 2          | 1 x S3B-PH-K-S<br>1 x PHR-3<br>3 x SPH-002T-P0.5S<br>3 x Braided 24 AWG | Wire colors and order given on sheet 2 (use yellow, black, & red wires)                |  |  |
| 3          | 1 x S4B-PH-K-S<br>1 x PHR-4<br>4 x SPH-002T-P0.5S<br>4 x Braided 24 AWG | Wire colors and order given on sheet 2 (use yellow, black, red, and blue wires)        |  |  |
| 4          | 1 x S5B-PH-K-S<br>1 x PHR-5<br>5 x SPH-002T-P0.5S<br>5 x Braided 24 AWG | Wire colors and order given on sheet 2 (use yellow, black, red, blue, and green wires) |  |  |
|            |   |  | Tolerances,<br>Unless noted-<br>0.0 +/-<br>0.000 +/- |  |
|            |   | JST_3-PIN_WITH_WIREOUTS  |  |  |
|            |   | Drawn by Spark Fun Electronics for   |  |  |
|            |   | Drafter  | Scale  |  |

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SparkFun Electronics: PRT-09914 PRT-09916