

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTLS8M00G56-B0 from the official website of Murata Manufacturing.


Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=CSTLS8M00G56-B0

CSTLS8M00G56-B0

In Production Recommended RoHS REACH

Appearance & Shape







Other Usage	Consumer/Industrial
-------------	---------------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
B0	Bulk	500



MURATA's ceramic resonator, CERALOCK(R) with built-in load capacitors, has been widely applied as the most suitable component for clock oscillators in a broad range of microprocessors. The CSTLS series can be used in the design of oscillation circuits not requiring external load capacitors, enabling both high-density mounting and cost reduction.

Features

1. Oscillation circuits do not require external load capacitors. There is some variation in built-in capacitance values applicable to various IC.

2. Stable over a wide temperature range.

3. Compact, lightweight and exhibit superior shock resistance performance.

- 4. Enable the design of oscillator circuits requiring no adjustment.
- 5. Cost-effective and reliable availability.

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of CSTLS8M00G56-B0 from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=CSTLS8M00G56-B0

CSTLS8M00G56-B0

Specifications

Product Type	Ceramic Resonator (CERALOCK®)	
Series	CSTLS_G	
Frequency	8.000MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature Range	-20°C to 80°C	
Frequency Shift by Temperature	-0.40 to +0.20%	
Frequency Aging	+/-0.20% max.	
Resonant Impedance (R1)	25ohm max.	
Built-in Load Capacitance(CL1/CL2)	47pF	
Shape	Lead	
Wash	Not available	

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

2 of 2